

# KOYO UCT206-19E bearing units

KOYO UCT206-19E bearing units 180 Outer Diameter (mm) Product Brochures 120 Bore Diameter (mm) , Manufacturing Service 120x180x28 Size (mm) . Get Your Free.

Size (mm)	120x180x28
Bore Diameter (mm)	120
Outer Diameter (mm)	180
Width (mm)	28
d	120 mm
D	180 mm
B	28 mm
C	28 mm
r min.	2 mm
da min.	129 mm
da max	136 mm
Da max.	171 mm
ra max.	2 mm
Weight	2,07 Kg
Basic dynamic load rating (C)	85 kN
Basic static load rating (C0)	79,5 kN
Reference speed	2 100 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359551198
Product Group	B00308

Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	120MM Bore; 180MM Outside Diameter; 28MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; N
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricat
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	4.56
Outside Diameter	7.087 Inch   180 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore	4.724 Inch   120 Millimeter
Outer Race Width	1.102 Inch   28 Millimeter
bore diameter:	120 mm
precision rating:	ISO Class 0
outside diameter:	180 mm

finish/coating:	Uncoated
overall width:	28 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	28 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	2100 rpm
internal clearance:	CN
fillet radius:	2 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	4100 RPM
dynamic load capacity:	85000 N
series:	60
static load capacity:	79500 N
manufacturer product page:	<a href="#">Click here</a>