

KOYO UCX10L3 deep groove ball bearings

Browse KOYO UCX10L3 deep groove ball bearings Categories in the 13 mm B Manufacturers Online Free. 32 mm d including .

d	32 mm
D	58 mm
B	13 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.13 kg
Dynamic load, C	11.8 kN
Static load, C0	8.05 kN
Fatigue limit load, Cu	0.37 kN
f0	15.4
Nlim (grease)	7,200 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
da min	37 mm
da max	39 mm
Da max	53 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.133

Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 3 ISO P6
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Steel
Rolling Element	Ball Bearing
Enclosure Type	Contact Seal
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row Deep Groove C3 Clearance
Long Description	32MM Bore; 58MM Outside Diameter; 13MM Width; 2 Seals Enclosure; ABEC 3 ISO P6 Precision; Steel Ba
UNSPSC	31171502
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball Deep Groove
Bore	1.26 Inch 32 Millimeter
Outside Diameter	2.283 Inch 58 Millimeter
Width	0.512 Inch 13 Millimeter