

# Large Turntable Ball Slewing Bearing Bearing for Plastic Extruder 010.25.1502

Request A Quote For Your Special Large Turntable Ball Slewing Bearing Bearing for Plastic Extruder 010.25.1502 10x26x8 Size (mm) Needs Today! Free 26 Outer Diameter (mm) Quotes. ISO 9001 10 Bore Diameter (mm) certified.

Size (mm)	10x26x8
Bore Diameter (mm)	10
Outer Diameter (mm)	26
Width (mm)	8
d	10 mm
D	26 mm
B	8 mm
C	8 mm
Angle ( $\alpha$ )	25 °
a	9 mm
r min.	0,3 mm
r1 min.	0,15 mm
da min.	12,5 mm
db min	12,5 mm
ra max.	0,3 mm
Weight	0,023 Kg
Basic dynamic load rating (C)	4,65 kN
Basic static load rating (C0)	2,07 kN
(Grease) Lubrication Speed	29 000 r/min
Contact angle $\alpha$	30 °

rs min	0.3 mm
r1s min	0.15 mm
Mass	0.02 kg
Dynamic load, C	4.65 kN
Static load, C0	2.07 kN
Fatigue limit load, Cu	0.09 kN
Nlim (oil)	39,000 rpm
Nlim (grease)	29,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	12.5 mm
Da max	23.5 mm
Db max	24.8 mm
r1a max	0.15 mm
ra max	0.15 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.021
EAN	4547359425420
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel

Contact Angle	30 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Ball
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7000
Bore	0.394 Inch   10 Millimeter
Outside Diameter	1.024 Inch   26 Millimeter
Width	0.315 Inch   8 Millimeter