

Loader Parts Slewing Bearing Swing Ring Qn2000.50A

Request A Quote For Your 120 mm D Special 65 mm d Loader Parts Slewing Bearing Swing Ring Qn2000.50A Needs Today! Free Quotes. ISO 9001 certified.

d	65 mm
D	120 mm
B	23 mm
E	105.6 mm
F	79.6 mm
rs min	1.5 mm
r1s min	1.5 mm
Radial clearance class	C3
Mass (without HJ ring)	1.05 kg
Dynamic load, C	84 kN
Static load, C0	94.5 kN
Fatigue limit load, Cu	11.5 kN
Nlim (oil)	7,000 rpm
Nlim (grease)	5,900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	73 mm
da max	77 mm
db min	81 mm
Da max	112 mm

ra max	1.5 mm
r1a max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.06
EAN	4547359139303
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage On Outer Ring ID
Long Description	65MM Bore; Straight Bore Profile; 120MM Outside Diameter; 23MM Width; Steel Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00

Noun	Bearing
Manufacturer Item Number	NU213C3
Weight / LBS	2.327
Bore	2.559 Inch 65 Millimeter
Width	0.906 Inch 23 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter