

Loyal 8067500 bearing

Manufacturers of all are represented in our partial list of clients. Contact Gary for a Mounted Bearing Engineering Group complete Loyal 8067500 bearing list of clients and projects.

| | |
|--------------------------|-----------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 2-7/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QVVPXT14V207SB |
| Locking Style | Double V-Lock |
| Weight | 22.00 lb |
| Housing Style | Two-Bolt Pillow Block |
| UPC Code | 0883450374255 |
| Dimension A | 3.00 in |
| Dimension B | 6.05 in |
| Dimension C | 3.7 in |
| Dimension D Max | 8.78 in |
| Dimension D Min | 7.66 in |
| Dimension F | 11.25 in |
| Dimension G | 2.900 in |
| Dimension H | 1.38 in |
| Dimension J (Bolt Size) | 0.750 in |
| Dimension L | 3.50 in |
| Dimension RVV | 0.60 in |
| Dimension SVV | 4.09 in |
| C – Dynamic Load (Basic) | 47800 lb |
| C0 – Static Load | 52000 lb |
| e – Geometry Factor | 0.23 |

| | |
|-------------------------------------|-----------|
| Y1 – Geometry Factor | 2.90 |
| Y2 – Geometry Factor | 4.32 |
| Oil Lubrication – M/N Seal | 1700 rpm |
| Oil Lubrication – T Seal | 3050 rpm |
| Oil Lubrication – B/C/O Seal | 1400 rpm |
| Grease Lubrication – M/N Seal | 1700 rpm |
| Grease Lubrication – T Seal | 2600 rpm |
| Grease Lubrication – B/C/O Seal | 1400 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0030 |
| Eng Internal Radial Clearance – Max | 0.0037 |
| Pre Install Clearance Min | 0.0030 in |
| Pre Install Clearance Max | 0.0037 in |