

Loyal Car skid turntable slewing bearings

Loyal Car skid turntable slewing bearings Industries and N/A
Minimum Buy Quantity Applications ? We sell discount online as well as 0.0 Inventory cheap machinery parts.

| | |
|---------------------------|-----------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 1.587 lb |
| EAN | 0087796057845 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Set Screw |
| Housing Style | 2 Bolt Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 11.5 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | GYAE30RRB |
| Seals | Double Land Riding Rubber Contact |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Metric |

| | |
|------------------------------------|--|
| Long Description | 2 Bolt Flange Block; 30MM Bore; 117MM Bolt Circle; 116.7MM Bolt Spacing; 1 Piece Solid; Set Screw Mo |
| Other Features | Single Row Normal Duty Narrow Inner Race |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer Item Number | SCJT 30 |
| Weight / LBS | 1.58 |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Nominal Bolt Circle Diameter Round | 4.6 Inch 117 Millimeter |
| Bolt Spacing | 4.594 Inch 116.7 Millimeter |
| d | 1.181 Inch 30 Millimeter |
| D | 1.28 Inch 32.5 Millimeter |
| Shaft Size d | 1.181 in |
| Bearing Type | Ball Bearing |
| Dimension E | 1.343 in |
| Inside Ring Outside Diameter | 1.579 in |
| Series | Standard |
| Seal Type | Narrow Shroud |
| Total Length H | 141.3 mm |
| Total Height L | 79.4 mm |
| Housing Width A | 0.843 in |
| Bolt Hole Spacing J | 116.68 mm |

| | |
|---------------------------------------|----------|
| Bolt Hole Size N | 11.5 mm |
| Flange Thickness A1 | 13.5 mm |
| Center of Bearing from Housing End A2 | 11.1 mm |
| Inside Ring Width B | 32.5 mm |
| Center of Bearing from Bearing End S | 11.1 mm |
| Static Load Rating | 2530 lbf |
| Dynamic Load Rating | 4850 lbf |