

Loyal CRBF108ATUU crossed roller bearing with mounting holes

Loyal CRBF108ATUU crossed roller bearing with mounting holes Engineering 80 Outer Diameter (mm) Calculator , Manufacturing Service . Get Your 210x80x159.9 Size (mm) Free.

Size (mm)	210x80x159.9
Bore Diameter (mm)	210
Outer Diameter (mm)	80
Width (mm)	159,9
d	80 mm
D	210 mm
H	159.9 mm
H1	176 mm
D1	103 mm
D2	155 mm
D3	220 mm
B	33 mm
C	27 mm
R	125 mm
s	43.5 mm
r1,2 – min.	3 mm
r3,4 – min.	1.1 mm
da	100 mm
Da – max.	155 mm
ra – max.	2.5 mm

rb – max.	1 mm
Basic dynamic load rating – C	371 kN
Basic static load rating – C0	1060 kN
Fatigue load limit – Pu	31.5 kN
Reference speed	700 r/min
Limiting speed	950 r/min
Minimum load factor – A	5.8
D1 ≈	103 mm
r1,2 min.	3 mm
r3,4 min.	1.1 mm
Da max.	155 mm
ra max.	2.5 mm
rb max.	1 mm
Basic dynamic load rating C	371 kN
Basic static load rating C0	1060 kN
Fatigue load limit Pu	31.5 kN
Minimum load factor A	5.8
Mass bearing (including seat washer where applicable)	29 kg