## Loyal CSF25-XRB Harmonic Driver High rigidity crossed roller Bearing

Online 0.0 Inventory shopping Loyal CSF25-XRB Harmonic Driver High rigidity crossed roller Bearing from a IPTCI BEARINGS Manufacturer Name great selection at Store. N/A Minimum Buy Quantity ... Accessories.

| Inventory                 | 0.0                        |
|---------------------------|----------------------------|
| Manufacturer Name         | IPTCI BEARINGS             |
| Minimum Buy Quantity      | N/A                        |
| Weight                    | 8.4                        |
| Product Group             | M06110                     |
| Number of Mounting Holes  | 4                          |
| Mounting Method           | Set Screw                  |
| Housing Style             | 4 Bolt Square Flange Block |
| Rolling Element           | Ball Bearing               |
| Housing Material          | Cast Iron                  |
| Expansion / Non-expansion | Non-expansion              |
| Mounting Bolts            | 11/16 Inch                 |
| Relubricatable            | Yes                        |
| Insert Part Number        | UCX15-48                   |
| Seals                     | B Seal                     |
| Housing Configuration     | 1 Piece Solid              |
| Pilot Configuration       | No Pilot                   |
| Inch — Metric             | Inch                       |
|                           |                            |

| Long Description                      | <pre>4 Bolt Square Flange Block;<br/>3" Bore; 8-1/2" Bolt Circle;<br/>6" Bolt Spacing; 1 Piece Sol</pre> |
|---------------------------------------|--|
| Other Features                        | Single Row   Spherical  <br>Medium Duty   Wide Inner Race  |
| UNSPSC                                | 31171501   |
| Harmonized Tariff Code                | 8483.20.40.40  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | UCFX 15 48   |
| Weight / LBS                          | 18.5   |
| d                                     | 3 Inch   76.2 Millimeter   |
| Nominal Bolt Circle Diameter<br>Round | 8.5 Inch   215 Millimeter  |
| D                                     | 3.252 Inch   82.6 Millimeter   |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter  |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter  |
| Bolt Spacing                          | 6 Inch   152.4 Millimeter  |