

# Loyal CSF25-XRB high rigid turntable bearings for industrial robot

100% Authentic. Loyal CSF25-XRB high rigid turntable bearings for industrial robot Highest N/A Minimum Buy Quantity Quality. Certified 0.0 Inventory Supplier.

|                           |                            |
|---------------------------|----------------------------|
| Inventory                 | 0.0                        |
| Manufacturer Name         | TIMKEN                     |
| Minimum Buy Quantity      | N/A                        |
| Weight                    | 18.16                      |
| EAN                       | 0883450280136              |
| Product Group             | M06288                     |
| Number of Mounting Holes  | 4                          |
| Mounting Method           | V Lock                     |
| Housing Style             | 4 Bolt Square Flange Block |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel                 |
| Expansion / Non-expansion | Expansion                  |
| Mounting Bolts            | 3/4 Inch                   |
| Relubricatable            | Yes                        |
| Insert Part Number        | 22220                      |
| Seals                     | Double Lip Viton           |
| Housing Configuration     | 1 Piece Solid              |
| Pilot Configuration       | No Pilot                   |
| Inch – Metric             | Metric                     |

|                                    |  |
|------------------------------------|--|
| Long Description                   | 4 Bolt Square Flange Block; 85MM Bore; 279.4MM Bolt Circle; 197.866MM Bolt Spacing; 1 Piece Solid; V |
| Other Features                     | Double Row   Double Nut  |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.80  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Weight / LBS                       | 40   |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter  |
| Bolt Spacing                       | 7.79 Inch   197.866 Millimeter   |
| D                                  | 4.62 Inch   117.348 Millimeter   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter  |
| d                                  | 3.346 Inch   85 Millimeter   |
| Nominal Bolt Circle Diameter Round | 11 Inch   279.4 Millimeter   |