

# Loyal RB12016 crossed roller bearing

170 Million used Loyal RB12016 crossed roller bearing instantly searchable. N/A Minimum Buy Quantity Shop our large selection of parts based on brand, 0.0 Inventory price, description, and location. Order the with stock ...

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 10.805   |
| EAN                       | 0698210003012  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 2207U  |
| Seals                     | Clearance Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Collar   Two Open Auxiliary End Cap   With Set Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 2-7/16" Bore; 2-3/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | AZEP2207  |
| Manufacturer Internal Number  | .   |
| Weight / LBS                  | 23.8  |
| B                             | 2.75 Inch   69.85 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| Bolt Spacing Maximum          | 8.75 Inch   222.25Millimeter  |
| d                             | 2.438 Inch   61.925 Millimeter  |
| D                             | 3.5 Inch   88.9 Millimeter  |
| Nominal Bolt Center to Center | 7.8 Inch   199.2 Millimeter   |
| Bolt Spacing Minimum          | 6.938 Inch   176.225Millimeter  |