

# Loyal RKS.062.25.1204 Medium size four-point contact ball slewing bearing with an internal gear

Loyal RKS.062.25.1204 Medium size four-point contact ball slewing bearing with an internal gear SEARCH – IPTCI BEARINGS Manufacturer Name N/A Minimum Buy Quantity Whether it's agriculture or construction equipment your working on, 0.0 Inventory Has the you need.

|                           |                            |
|---------------------------|----------------------------|
| Inventory                 | 0.0                        |
| Manufacturer Name         | IPTCI BEARINGS             |
| Minimum Buy Quantity      | N/A                        |
| Weight                    | 2.54                       |
| Product Group             | M06110                     |
| Number of Mounting Holes  | 4                          |
| Mounting Method           | Set Screw                  |
| Housing Style             | 4 Bolt Square Flange Block |
| Rolling Element           | Ball Bearing               |
| Housing Material          | Nickel Coated Cast Iron    |
| Expansion / Non-expansion | Non-expansion              |
| Mounting Bolts            | 9/16 Inch                  |
| Relubricatable            | Yes                        |
| Insert Part Number        | SUC210-32                  |
| Seals                     | B Seal                     |
| Housing Configuration     | 1 Piece Solid              |
| Pilot Configuration       | No Pilot                   |

|                                    |  |
|------------------------------------|--|
| Inch – Metric                      | Inch   |
| Long Description                   | 4 Bolt Square Flange Block; 2" Bore; 6.2" Bolt Circle; 4-3/8" Bolt Spacing; 1 Piece S                |
| Other Features                     | Single Row   Spherical   Corrosion Resistant   Stainless Steel Insert   Has Slinger   Optional Locki |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | SUCNPF 210 32  |
| Weight / LBS                       | 5.6  |
| Bolt Spacing                       | 4.375 Inch   111.13 Millimeter   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter  |
| Nominal Bolt Circle Diameter Round | 6.2 Inch   157 Millimeter  |
| d                                  | 2 Inch   50.8 Millimeter   |
| D                                  | 2.032 Inch   51.613 Millimeter   |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter  |