Loyal RKS.062.25.1754 Medium size four-point contact ball slewing bearing with an internal gear

We 5 in Shaft Size Provide Extensive Loyal RKS.062.25.1754 Medium size four-point contact ball slewing bearing with an internal gear Mounted Bearing Engineering Group Selection And Competitive Wholesale Pricing.

| Engineering Group | Mounted Bearing |
|-------------------------|-------------------|
| Shaft Size | 5 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | 99999B |
| Locking Style | Double Concentric |
| Weight | 115 lb |
| Housing Style | Round Flange |
| UPC Code | 0883450301664 |
| Dimension BC | 14.00 in |
| Dimension C | 6.890 in |
| Dimension D | 7.63 in |
| Dimension E | 7.000 in |
| Dimension F | 8.38 in |
| Dimension H | 1.50 in |
| Dimension J (Bolt Size) | 1.125 in |
| Dimension L Exp | 4.3 in |
| Dimension L Fix | 4.22 in |
| Dimension M | 2.59 in |

| Dimension N | 5.320 in |
|-------------------------------------|-----------|
| Dimension R | 0.97 in |
| Dimension S | 5.18 in |
| CO — Static Load | 212000 lb |
| C — Dynamic Load (Basic) | 170000 lb |
| e — Geometry Factor | 0.26 |
| Y1 - Geometry Factor | 2.43 |
| Y2 - Geometry Factor | 3.61 |
| Oil Lubrication — M/N Seal | 700 rpm |
| Oil Lubrication — T Seal | 1500 rpm |
| Oil Lubrication — B/C/O Seal | 400 rpm |
| Grease Lubrication — M/N Seal | 700 rpm |
| Grease Lubrication — T Seal | 1000 rpm |
| Grease Lubrication — B/C/O Seal | 400 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0050 in |
| Eng Internal Radial Clearance — Min | 0.0037 |
| Eng Internal Radial Clearance — Max | 0.0057 |
| Pre Install Clearance Min | 0.095 mm |
| Pre Install Clearance Max | 0.145 mm |