

Loyal RU42 Crossed Roller Bearing

Online Loyal RU42 Crossed Roller Bearing Expert. More Choices. Loyal RU42 Crossed Roller Bearing in Stock & Ready to 19x7x6 Size (mm) Ship Now!

Size (mm)	19x7x6
Bore Diameter (mm)	19
Outer Diameter (mm)	7
Width (mm)	6
d	7 mm
D	19 mm
B	6 mm
d1	10.4 mm
d2	9.9 mm
D1	15.7 mm
r1,2 – min.	0.3 mm
r3,4 – min.	0.15 mm
a	4.8 mm
da – min.	9 mm
db – min.	9 mm
Da – max.	17 mm
Db – max.	17.6 mm
ra – max.	0.3 mm
rb – max.	0.15 mm
dn	11.4 mm
Basic dynamic load rating – C	2 kN
Basic static load rating – C0	0.64 kN

Fatigue load limit – Pu	0.027 kN
Limiting speed for grease lubrication	127000 r/min
Limiting speed for oil lubrication	190000 mm/min
Ball – Dw	3.572 mm
Ball – z	8
Gref	0.11 cm ³
Calculation factor – f ₀	6.5
Preload class A – GA	10 N
Preload class B – GB	30 N
Preload class C – GC	60 N
Calculation factor – f	1
Calculation factor – f _{2A}	1
Calculation factor – f _{2B}	1.03
Calculation factor – f _{2C}	1.05
Calculation factor – f _{HC}	1
Preload class A	8 N/micron
Preload class B	13 N/micron
Preload class C	18 N/micron
r _{1,2} min.	0.3 mm
r _{3,4} min.	0.15 mm
d _a min.	9 mm
d _b min.	9 mm
D _a max.	17 mm
D _b max.	17.6 mm
r _a max.	0.3 mm
r _b max.	0.15 mm
Basic dynamic load rating C	1.95 kN
Basic static load rating C ₀	0.64 kN
Fatigue load limit Pu	0.027 kN

Attainable speed for grease lubrication	127000 r/min
Attainable speed for oil-air lubrication	190000 r/min
Ball diameter D_w	3.572 mm
Number of balls z	8
Reference grease quantity G_{ref}	0.11 cm ³
Preload class A G_A	10 N
Static axial stiffness, preload class A	8 N/ μ m
Preload class B G_B	30 N
Static axial stiffness, preload class B	13 N/ μ m
Preload class C G_C	60 N
Static axial stiffness, preload class C	18 N/ μ m
Calculation factor f	1.02
Calculation factor f_1	1
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.03
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1
Calculation factor f_0	6.5
Mass bearing	0.007 kg