

Loyal VSI200544-N INA spec slewing ring deck crane

How do 25 mm d you find the Loyal VSI200544-N INA spec slewing ring deck crane specification? Manufacturers Online Free check□
24 mm B

d	25 mm
D	62 mm
B	24 mm
C	20 mm
T	25.25 mm
d1	42.5 mm
a	16 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.3
Y2	2
Y0	1.1
Mass	0.38 kg
ISO 355 reference	T2FD025
Dynamic load, C	61.5 kN
Rating life coefficient, A2	1.9
Static load, C0	64.5 kN
Fatigue limit load, Cu	7.9 kN
Nlim (oil)	8,900 rpm
Nlim (grease)	6,700 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.43 Hz
Characteristic outer ring frequency, BPF0	5.13 Hz
Characteristic inner ring frequency, BRFI	7.87 Hz
da max	32 mm
db min	33.5 mm
Da min	52 mm
Da max	53.5 mm
Db min	57 mm
Ca min	3 mm
Cb min	5 mm
ra max	1.5 mm
r1a max	1.5 mm