

# Loyal XSA140544-N Crossed roller slewing bearings

Shop Loyal XSA140544-N Crossed roller slewing bearings huge online discount inventory. 15x35x20 Size (mm) and Import machinery parts your car needs 15,000 Bore Diameter (mm) with Free Shipping and Free Extended Warranty.

|                                 |                 |
|---------------------------------|-----------------|
| Size (mm)                       | 15x35x20        |
| Bore Diameter (mm)              | 15,000          |
| Outer Diameter (mm)             | 35,000          |
| Width (mm)                      | 20,000          |
| d                               | 15,000 mm       |
| D                               | 35,000 mm       |
| B                               | 20,000 mm       |
| C                               | 20,000 mm       |
| Inventory                       | 0.0             |
| Manufacturer Name               | NTN             |
| Minimum Buy Quantity            | N/A             |
| Weight / Kilogram               | 0.086           |
| Product Group                   | B00152          |
| Enclosure                       | 2 Seals         |
| Flush Ground                    | No              |
| Rolling Element                 | Ball Bearing    |
| Number of Rows of Balls         | Double Row      |
| Precision Class                 | ABEC 1   ISO P0 |
| Maximum Capacity / Filling Slot | No              |
| Snap Ring                       | No              |

|                        |   |
|------------------------|---|
| Internal Clearance     | C0-Medium   |
| Number of Bearings     | 1 (Single)  |
| Inch – Metric          | Metric  |
| Long Description       | 15MM Bore; 35MM Outside Diameter; 20MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of |
| Other Features         | Polyacrylic Friction Seal   |
| UNSPSC                 | 31171531  |
| Harmonized Tariff Code | 8482.10.50.28   |
| Noun                   | Bearing   |
| Keyword String         | Angular Contact   |
| Weight / LBS           | 0.176   |
| Bore                   | 0.591 Inch   15 Millimeter  |
| Width                  | 0.787 Inch   20 Millimeter  |
| Outside Diameter       | 1.378 Inch   35 Millimeter  |