

# Loyal XU080120 Crossed roller slewing bearings (without gear teeth)

Welcome to 200.025 mm da the 117.805 mm Ca Loyal XU080120 Crossed roller slewing bearings (without gear teeth) online seller.

da	200.025 mm
Da	399.999 mm
Ca	117.805 mm
A1	222.25 mm
A2	368.3 mm
S	4.763 mm
ba	90.487 mm
H	474.663 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	79.375 mm

Housing	SAF 544
Bearing	22244 CCK/W33
Adapter sleeve assembly	SNW 44×7.7/8
Stabilizing ring	SR-44-38
Taconite seal	TER 166
End plug (suffix Y)	EPR 23
Max. speed for Taconite seal	385 r/min
P60°	423 kN
P90°	254 kN
P120°	160 kN
P150°	145 kN
P180°	173 kN
Pa	71.2 kN
Mass pillow block	262 kg
Cap bolt	4 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g