

# LS GEFZ22S plain bearings

Can't find what you're looking for 110 mm da LS GEFZ22S plain bearings ? Our expert Representatives be in contact with you shortly!

|         |            |
|---------|------------|
| da      | 110 mm     |
| db      | 123.825 mm |
| dc      | 106.362 mm |
| Da      | 200 mm     |
| Ca      | 62.789 mm  |
| A1      | 120.65 mm  |
| A2      | 165.1 mm   |
| S       | 4.763 mm   |
| ba      | 50.006 mm  |
| H       | 239.316 mm |
| H1      | 125.425 mm |
| H2      | 50.8 mm    |
| J min.  | 320.675 mm |
| J max.  | 368.3 mm   |
| J1      | 69.85 mm   |
| L       | 419.1 mm   |
| N1      | 22.225 mm  |
| R1      | 67.866 mm  |
| R2      | 31.75 mm   |
| RG      | 3/8 NPT    |
| PG      | 1/4 NPT    |
| h       | 45.244 mm  |
| Housing | SAF 222    |

|                                                   |                |
|---------------------------------------------------|----------------|
| Bearing                                           | 22222 E        |
| Lock nut                                          | AN 22          |
| Lock washer                                       | W 22           |
| Stabilizing ring                                  | SR-22-19       |
| Labyrinth ring (db shaft position)                | LOR 121        |
| PosiTrac Plus contact element (db shaft position) | B10724-122     |
| Labyrinth ring (dc shaft position)                | LOR 113        |
| PosiTrac Plus contact element (dc shaft position) | B10724-113     |
| End plug (suffix Y)                               | EPR 14         |
| Max. speed for PosiTrac Plus seal                 | 1150 r/min     |
| P60°                                              | 149 kN         |
| P90°                                              | 89 kN          |
| P120°                                             | 55.6 kN        |
| P150°                                             | 50.7 kN        |
| P180°                                             | 60.9 kN        |
| Pa                                                | 39.6 kN        |
| Mass pillow block                                 | 30.7 kg        |
| Cap bolt                                          | 2 x 3/4-10 UNC |
| Cap bolt recommended tightening torque            | 203.4 N·m      |
| Cap bolt, SAE grade                               | 5              |
| Appropriate attachment bolt size G                | 0.75 in        |
| Initial grease fill                               | 481.95 g       |