

# LS GEH100XT-2RS plain bearings

LET OUR LS GEH100XT-2RS plain bearings 0.0 Inventory EXPERTS GET YOU TIMKEN Manufacturer Name THE PARTS YOU NEED.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 56.296   |
| EAN                       | 0883450343459  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22228  |
| Seals                     | Teflon Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Nut   SN Style   |
| Long Description          | 4 Bolt Pillow Block; 5" Bore; 5-29/32" Base to Center Height; V Lock Mount; Spherical Roll |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Weight / LBS                  | 124                            |
| B                             | 5.906 Inch   150 Millimeter    |
| Bolt Spacing Minimum          | 15.01 Inch   381.254Millimeter |
| Nominal Bolt Center to Center | 16.4 Inch   416.6 Millimeter   |
| D                             | 5.82 Inch   147.828 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| d                             | 5 Inch   127 Millimeter        |
| Bolt Spacing Maximum          | 17.66 Inch   448.564Millimeter |