

LS GEZ101ES plain bearings

What are the types of LS GEZ101ES plain bearings ?
Manufacturing Service 57.15 mm da . Get Your Free, Instant price, design review.

da	57.15 mm
Da	140 mm
Ca	57.785 mm
A1	88.9 mm
A2	209.55 mm
S	4.763 mm
ba	40.481 mm
H	167.481 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
N1	22.225 mm
R1	53.181 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	35.719 mm
Housing	SAF 613
Bearing	22313 EK
Adapter sleeve assembly	SNW 113×2.1/4
Stabilizing ring	SR-16-13

Taconite seal	TER 33
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1400 r/min
P60°	83.2 kN
P90°	49.8 kN
P120°	30.2 kN
P150°	26.7 kN
P180°	31.6 kN
Pa	9.43 kN
Mass pillow block	19 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	87.885 g