

LS GEZ152ET-2RS plain bearings

How do 35 Outer Diameter (mm) I place an EMERGENCY order for a LS GEZ152ET-2RS plain bearings that I 55x35x10 Size (mm) want to pick up at a our store?

Size (mm)	55x35x10
Bore Diameter (mm)	55
Outer Diameter (mm)	35
Width (mm)	10
d	35 mm
D	55 mm
B	10 mm
d1	41.7 mm
d2	40.2 mm
D2	50.3 mm
r1,2 – min.	0.6 mm
r3,4 – min.	0.3 mm
a	11.4 mm
da – min.	38.2 mm
da – max.	41.3 mm
db – min.	37 mm
db – max.	39.8 mm
Da – max.	51.8 mm
Db – max.	53 mm
ra – max.	0.6 mm
rb – max.	0.3 mm
Basic dynamic load rating – C	7.6 kN

Basic static load rating – C0	4.8 kN
Fatigue load limit – Pu	0.2 kN
Limiting speed for grease lubrication	36000 r/min
Ball – Dw	5.556 mm
Ball – z	19
Calculation factor – f0	8.3
Preload class A – GA	41 N
Preload class B – GB	125 N
Preload class C – GC	250 N
Calculation factor – f	1
Calculation factor – f2A	1
Calculation factor – f2B	1.04
Calculation factor – f2C	1.08
Calculation factor – fHC	1
Preload class A	28 N/micron
Preload class B	43 N/micron
Preload class C	59 N/micron
r1,2 min.	0.6 mm
r3,4 min.	0.3 mm
da min.	38.2 mm
da max.	41.3 mm
db min.	37 mm
db max.	39.8 mm
Da max.	51.8 mm
Db max.	53 mm
ra max.	0.6 mm
rb max.	0.3 mm
Basic dynamic load rating C	7.61 kN
Basic static load rating C0	4.75 kN

Fatigue load limit P_u	0.2 kN
Attainable speed for grease lubrication	36000 r/min
Ball diameter D_w	5.556 mm
Number of balls z	19
Preload class A G_A	41 N
Static axial stiffness, preload class A	28 N/ μm
Preload class B G_B	125 N
Static axial stiffness, preload class B	43 N/ μm
Preload class C G_C	250 N
Static axial stiffness, preload class C	59 N/ μm
Calculation factor f	1.05
Calculation factor f_1	1
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.04
Calculation factor f_{2C}	1.08
Calculation factor f_{HC}	1
Calculation factor f_0	8.3
Mass bearing	0.074 kg