

# LS GX70N plain bearings

LS GX70N plain bearings with easy-to-use 15x28x7 Size (mm) parts graphics, giving you the ability to check parts 28 Outer Diameter (mm) availability, pricing, examine remanufactured 15 Bore Diameter (mm) options.

Size (mm)	15x28x7
Bore Diameter (mm)	15
Outer Diameter (mm)	28
Width (mm)	7
d	15 mm
D	28 mm
B	7 mm
C	7 mm
r min.	0,3 mm
da min.	17 mm
da max	17,5 mm
Da max.	26 mm
ra max.	0,3 mm
Weight	0,016 Kg
Basic dynamic load rating (C)	3,65 kN
Basic static load rating (C0)	2 kN
(Grease) Lubrication Speed	24 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.016
Product Group	B00308
Enclosure	2 Seals

Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No F
Other Features	Deep Groove   Non-Friction Nitrile Rubber Seal   Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.037
Outside Diameter	1.102 Inch   28 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Bore	0.591 Inch   15 Millimeter