

NACHI 22210AEX cylindrical roller bearings

NACHI 22210AEX cylindrical roller bearings TIMKEN Manufacturer Name with easy-to-use parts 0.0 Inventory graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

| | |
|---------------------------|---------------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 9.08 |
| EAN | 0883450275392 |
| Product Group | M06288 |
| Number of Mounting Holes | 2 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Steel |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22213 |
| Seals | Triple Lip Urethane |
| Housing Configuration | 1 Piece Solid |
| Inch – Metric | Metric |
| Other Features | Double Row Extreme Duty SAF Style |

| | |
|-------------------------------|---|
| Long Description | 2 Bolt Pillow Block; 60MM Bore; 76.2MM Base to Center Height; Tapered Adapter Sleeve Mount; Spherica |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | TAPA13K060SE0 |
| Weight / LBS | 23 |
| Bolt Spacing Minimum | 7.2 Inch 182.88Millimeter |
| B | 3 Inch 76.2 Millimeter |
| Bolt Spacing Maximum | 9.2 Inch 233.68Millimeter |
| Nominal Bolt Center to Center | 8.2 Inch 208.3 Millimeter |
| D | 2.56 Inch 65.024 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| d | 2.362 Inch 60 Millimeter |