

NACHI 22228EX cylindrical roller bearings

Manufacturers of all are 0.0 Inventory represented in our partial list N/A Minimum Buy Quantity of clients. Contact Gary for a complete NACHI 22228EX cylindrical roller bearings list of clients and projects.

| | |
|-------------------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight | 4.26 |
| EAN | 0029176411809 |
| Product Group | B04311 |
| Internal Clearance | C3-Loose |
| Mounting Method | Adapter Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Tapered |
| Cage Material | Steel |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Adapter Part Number – Millimeter | H2314 (Specify bore) |
| Withdrawal Sleeve | AH2314 (Specify bore) |
| Inch – Metric | Metric |
| Long Description | 70MM Tapered Bore; 150MM Outside Diameter; 51MM Width; C3-Loose Clearance; Adapter Mount; Double Row |

| | |
|------------------------------|---|
| Other Features | Order adapter or withdrawal sleeve or nut separately. Others may be available |
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |
| Manufacturer Item Number | 22314EAKE4C3 |
| Weight / LBS | 4.26 |
| d | 2.756 Inch 70 Millimeter |
| D | 5.906 Inch 150 Millimeter |
| B | 2.008 Inch 51 Millimeter |
| bore diameter: | 70 mm |
| maximum rpm: | 3800 RPM |
| outside diameter: | 150 mm |
| operating temperature range: | Maximum of +200 °C |
| overall width: | 51 mm |
| cage material: | Steel |
| bore type: | Tapered 1:12 |
| bearing material: | Steel |
| outer ring type: | Not Split |
| cage type: | Roller Guided |
| internal clearance: | C3 |
| precision rating: | RBEC 1 (ISO Class Normal) |
| closure type: | Open |
| finish/coating: | Uncoated |
| lubrication hole type: | Lubrication Groove & Hole |
| outer ring width: | 51 mm |
| dynamic load capacity: | 425000 N |

| | |
|-----------------------|----------|
| fillet radius: | 2.1 mm |
| static load capacity: | 435000 N |
| series: | 223 |