NACHI 23092EK cylindrical roller bearings

Online shopping NACHI 23092EK cylindrical roller bearings from Mounted Bearing Engineering Group 55 mm Shaft Size a great selection at Store. ... Accessories.

| Engineering Group | Mounted Bearing |
|-------------------------|-----------------------|
| Shaft Size | 55 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QAAP11A055SB |
| Locking Style | Double Concentric |
| Weight | 17.0 lb |
| Housing Style | Two-Bolt Pillow Block |
| UPC Code | 0883450286060 |
| Dimension A | 2.50 in |
| Dimension B | 5.25 in |
| Dimension C | 3.25 in |
| Dimension D Max | 7.88 in |
| Dimension D Min | 6.50 in |
| Dimension F | 9.63 in |
| Dimension G | 2.630 in |
| Dimension H | 1.25 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension L | 3.32 in |
| Dimension M | 2 in |
| Dimension RAA | 0.69 in |
| Dimension SAA | 4 in |
| CO — Static Load | 31900 lb |

| C — Dynamic Load (Basic) | 31400 lb |
|-------------------------------------|-----------|
| e — Geometry Factor | 0.23 |
| Y1 - Geometry Factor | 2.95 |
| Y2 - Geometry Factor | 4.40 |
| Oil Lubrication — M/N Seal | 2200 rpm |
| Oil Lubrication — T Seal | 3800 rpm |
| Oil Lubrication — B/C/O Seal | 1600 rpm |
| Grease Lubrication — M/N Seal | 2200 rpm |
| Grease Lubrication — T Seal | 3200 rpm |
| Grease Lubrication — B/C/O Seal | 1600 rpm |
| Float | 0.050 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance — Min | 0.0016 |
| Eng Internal Radial Clearance — Max | 0.0026 |
| Pre Install Clearance Min | 0.0016 in |
| Pre Install Clearance Max | 0.0026 in |