

NACHI 30RUSS4CS cylindrical roller bearings

Our 12x32x12.700 Size (mm) highly-skilled and factory-trained service experts have the resources to help you with all your NACHI 30RUSS4CS cylindrical roller bearings needs – including routine maintenance, major repairs, warranty service, and 12,000 Bore Diameter (mm) equipment inspections.

Size (mm)	12x32x12.700
Bore Diameter (mm)	12,000
Outer Diameter (mm)	32,000
Width (mm)	12,700
d	12,000 mm
D	32,000 mm
B	12,700 mm
C	12,700 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359614060
Product Group	B00308
Enclosure	1 Seal-1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Wide Inner Ring

Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	12MM Bore; 32MM Outside Diameter; 10MM Outer Race Width; 1 Seal-1 Metal Shield; Ball Bearing; ABEC 1
Other Features	Deep Groove Felt Seal Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.097
Bore	0.472 Inch 12 Millimeter
Inner Race Width	0.48 Inch 12.2 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
bore diameter:	12 mm
static load capacity:	2740 N
outside diameter:	32 mm
precision rating:	ISO Class 0
overall width:	12.7 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	One Seal/One Shield
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot

inner ring width:	12.192 mm
snap ring included:	Without Snap Ring
outer ring width:	10 mm
internal clearance:	CN
maximum rpm (grease):	16000 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	0.6 mm
dynamic load capacity:	6100 N
manufacturer product page:	Click here