

# NACHI 36RFSNX5C/47 cylindrical roller bearings

Shop NACHI 36RFSNX5C/47 cylindrical roller bearings huge online discount inventory. and Import machinery parts your car needs with Free Shipping and Free Extended 30 mm d Warranty.

d	30 mm
D	55 mm
B	13 mm
rs min	1 mm
Radial clearance class	CN
Mass	0.12 kg
Dynamic load, C	13.2 kN
Static load, C <sub>0</sub>	8.3 kN
Fatigue limit load, C <sub>u</sub>	0.38 kN
f <sub>0</sub>	14.8
N <sub>lim</sub> (oil)	15,000 rpm
N <sub>lim</sub> (grease)	13,000 rpm
Min operating temperature, T <sub>min</sub>	-20 °C
Max operating temperature, T <sub>max</sub>	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.85 Hz
Characteristic outer ring frequency, BPF <sub>0</sub>	4.59 Hz
Characteristic inner ring frequency, BPF <sub>I</sub>	6.41 Hz
da min	35 mm
Da max	50 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.109
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 55MM Outside Diameter; 13MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Fil
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.25
Outer Race Width	0.512 Inch   13 Millimeter
Bore	1.181 Inch   30 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	2.165 Inch   55 Millimeter