

NACHI 420KBE031 tapered roller bearings

100% Authentic. NACHI 420KBE031 tapered roller bearings 152.4 mm da Highest 119.812 mm Ca Quality. Certified Supplier.

da	152.4 mm
Da	309.999 mm
Ca	119.812 mm
A1	171.45 mm
A2	307.975 mm
S	4.763 mm
ba	86.519 mm
H	360.363 mm
H1	179.375 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	54.769 mm
Housing	SAW 534
Bearing	23234 CCK/W33
Adapter sleeve assembly	SNW 134×6

Stabilizing ring	SR-34-0
Taconite seal	TER 141
End plug (suffix Y)	EPR 18
Max. speed for Taconite seal	500 r/min
P60°	234 kN
P90°	140 kN
P120°	85.9 kN
P150°	77 kN
P180°	92.5 kN
Pa	56 kN
Mass pillow block	132 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g