

# NACHI 5218N angular contact ball bearings

170 Million 0.0 Inventory N/A Minimum Buy Quantity used NACHI 5218N angular contact ball bearings instantly searchable. Shop our large selection of parts REXNORD Manufacturer Name based on brand, price, description, and location. Order the with stock ...

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 17.252   |
| EAN                       | 0698210906788  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing                                     |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 22 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 2085MMU  |
| Seals                     | Clearance Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Normal Duty  <br>Single Collar   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 85MM Bore; 95MM Base to Center Height; Concentric Collar Mount; Spherical Rolle |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | ZA2085MM   |
| Manufacturer Internal Number  | 6890678  |
| Weight / LBS                  | 40.3   |
| D                             | 4.375 Inch   111.13 Millimeter   |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter   |
| d                             | 3.346 Inch   85 Millimeter   |
| B                             | 3.74 Inch   95 Millimeter  |
| Actual Bolt Center to Center  | 10 Inch   254Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter   |