

NACHI 6211ZZE deep groove ball bearings

We Provide Extensive 90x50x20 Size (mm) NACHI 6211ZZE deep groove ball bearings Selection And Competitive Wholesale Pricing.

Size (mm)	90x50x20
Bore Diameter (mm)	90
Outer Diameter (mm)	50
Width (mm)	20
d	50 mm
D	90 mm
B	20 mm
d1	62.51 mm
D2	81.61 mm
r1,2 – min.	1.1 mm
da – min.	57 mm
da – max.	62.4 mm
Da – max.	83 mm
ra – max.	1 mm
Basic dynamic load rating – C	37.1 kN
Basic static load rating – C0	23.2 kN
Limiting speed	60 r/min
Limiting temperature – T	250 °C
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.479

EAN	7316570900446
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Extreme Temperature Variant
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6210-2Z/VA201
Weight / LBS	0.47
Outer Race Width	0.787 Inch 20 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.969 Inch 50 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
bore diameter:	50 mm
precision rating:	Not Rated

outside diameter:	90 mm
finish/coating:	Uncoated
overall width:	20 mm
cage material:	Steel
bore type:	Round
outer ring width:	20 mm
closure type:	Double Shielded
fillet radius:	1.1 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	120 RPM
internal clearance:	C0
series:	62
operating temperature range:	-20 to +480 °F
resistance features:	Corrosion Resistant, Extreme Temperature
static load capacity:	23.2 kN
d1 ≈	62.51 mm
D2 ≈	81.61 mm
r1,2 min.	1.1 mm
da min.	57 mm
da max.	62.4 mm
Da max.	83 mm
ra max.	1 mm
Basic dynamic load rating C	37.1 kN
Basic static load rating C0	23.2 kN
Limiting temperature T max.	250 °C
Mass bearing	0.47 kg