

# NACHI 6809NSE deep groove ball bearings

NACHI 6809NSE deep groove ball bearings, Units and Housings CAD models , Manufacturing Service . Get 0.0 Inventory Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9.988  |
| EAN                       | 0883450238403  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Round Flange Cartridge  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22216  |
| Seals                     | Triple Lip Urethane  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>2-11/16" Bore; 7-1/2" Bolt<br>Circle; 5.3" Bolt Spacing; |

|                                       |                                |
|---------------------------------------|--------------------------------|
| Other Features                        | Double Row   Double Nut        |
| UNSPSC                                | 31171501                       |
| Harmonized Tariff Code                | 8483.20.40.80                  |
| Noun                                  | Bearing                        |
| Keyword String                        | Flanged                        |
| Weight / LBS                          | 22                             |
| D                                     | 4.08 Inch   103.632 Millimeter |
| Nominal Bolt Circle Diameter<br>Round | 7.5 Inch   190 Millimeter      |
| Cartridge Pilot Depth                 | 1.25 Inch   31.75 Millimeter   |
| Cartridge Pilot Diameter              | 6.375 Inch   161.92 Millimeter |
| Bolt Spacing                          | 5.3 Inch   134.7 Millimeter    |
| d                                     | 2.688 Inch   68.275 Millimeter |