

NACHI 7019CDF angular contact ball bearings

High Triple-lip seals Sealing solution Quality NACHI 7019CDF angular contact ball bearings. Competitive Steel/steel Design (sliding contact surface combination) Pricing. Regular relubrication – grease Lubricant Accept Small Order. Easy and Fast Shipping.

| | |
|--|--------------------------------|
| Lubricant | Regular relubrication – grease |
| Design (sliding contact surface combination) | Steel/steel |
| Sealing solution | Triple-lip seals |
| d | 152.4 mm |
| D | 222.25 mm |
| B | 209.55 mm |
| C | 104.775 mm |
| α | 5 ° |
| dk | 207.162 mm |
| d1 ≈ | 178.3 mm |
| b | 15 mm |
| b1 | 11 mm |
| M | 8 mm |
| r1 min. | 2 mm |
| r2 min. | 1.1 mm |
| da min. | 164 mm |
| da max. | 178.3 mm |
| Da min. | 197.5 mm |
| Da max. | 213.5 mm |

| | |
|--------------------------------|-----------------------|
| ra max. | 2 mm |
| rb max. | 1.1 mm |
| Basic dynamic load rating C | 1730 kN |
| Basic static load rating C0 | 5200 kN |
| Specific dynamic load factor K | 100 N/mm ² |
| Specific static load factor K0 | 300 N/mm ² |
| Material constant KM | 330 |
| Mass plain bearing | 21.5 kg |