

# NACHI 7024CDB angular contact ball bearings

offers a NACHI 7024CDB angular contact ball bearings selection N/A Minimum Buy Quantity of Genuine at Wholesale Prices. 0.0 Inventory We are a NACHI 7024CDB angular contact ball bearings Certified Parts Retailer

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | IPTCI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.408   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Thermoplastic   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | SNA205  |
| Seals                     | B Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Metric  |
| Other Features            | Single Row   Corrosion Resistant   Stainless Steel Insert   Has Slinger |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 25MM Bore; 36.5MM Base to Center Height; Eccentric Collar Mount; Ball Bearing; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.40   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | SNATP 205 25MM  |
| Weight / LBS                  | 0.9   |
| d                             | 0.984 Inch   25 Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |
| Actual Bolt Center to Center  | 4.1 Inch   105Millimeter  |
| D                             | 1.622 Inch   41.2 Millimeter  |
| B                             | 1.437 Inch   36.5 Millimeter  |
| Nominal Bolt Center to Center | 4.1 Inch   105 Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |