

NACHI 850R/832 tapered roller bearings

Welcome to 70x110x20 Size (mm) the NACHI 850R/832 tapered roller bearings online seller. 110 Outer Diameter (mm)

Size (mm)	70x110x20
Bore Diameter (mm)	70
Outer Diameter (mm)	110
Width (mm)	20
d	70 mm
D	110 mm
B	20 mm
C	20 mm
r min.	1.1 mm
da min.	76 mm
Da max.	104 mm
ra max.	1.0 mm
Weight	0.607 Kg
Basic dynamic load rating (C)	38 kN
Basic static load rating (C0)	31 kN
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No

Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	70MM Bore; 110MM Outside Diameter; 20MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 IS
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Bore	2.756 Inch 70 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	70 mm
Width	20 mm
Fillet Radius/Chamfer	1.1 mm
Dynamic Load Rating	38,000 N
Static Load Rating	31,000 N
Limiting Speed – Grease	6,100 rpm
Factor fo	15.6
Radial Clearance	0.010 to 0.030 mm
da (min)	76 mm

Da (max)	104 mm
ra (max)	1 mm