

# NACHI E32928J tapered roller bearings

With over 10170 full-service stores, 37 mm D our NACHI E32928J tapered roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize 12 mm d your productivity by saving time and your hard-earned dollars.

d	12 mm
D	37 mm
B	12 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.06 kg
Dynamic load, C	9.7 kN
Static load, C0	4.2 kN
Fatigue limit load, Cu	0.19 kN
f0	11.1
Nlim (grease)	20,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.34 Hz
Characteristic rolling element frequency, BSF	2.76 Hz
Characteristic outer ring frequency, BPF0	2.03 Hz
Characteristic inner ring frequency, BPFI	3.97 Hz

da min	17 mm
da max	18.5 mm
Da max	32 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.06
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	12MM Bore; 37MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Non-Friction Nitrile Rubber Seal   Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing

Keyword String	Ball
Weight / LBS	0.13227
Outer Race Width	0.472 Inch   12 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore	0.472 Inch   12 Millimeter
Outside Diameter	1.457 Inch   37 Millimeter