

# NACHI H-LM11949/H-LM11910 tapered roller bearings

YOU’LL FIND REXNORD Manufacturer Name AN EXTENSIVE SELECTION OF NACHI H-LM11949/H-LM11910 tapered roller bearings FOR 0.0 Inventory SALE.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 26.33   |
| EAN                       | 0698210017743   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 2 Bolt Pillow Block                                       |
| Rolling Element           | Spherical Roller Bearing                                  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 25 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | 2100MMU   |
| Seals                     | Clearance Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Metric  |
| Other Features            | Double Row   Normal Duty   Single Collar   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 100MM Bore; 104.8MM Base to Center Height; Concentric Collar Mount; Spherical R |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | ZA2100MM   |
| Manufacturer Internal Number  | 6801774  |
| Weight / LBS                  | 58   |
| d                             | 3.937 Inch   100 Millimeter  |
| Nominal Bolt Center to Center | 10.9 Inch   276.9 Millimeter   |
| Actual Bolt Center to Center  | 10.9 Inch   276.2Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter   |
| B                             | 4.126 Inch   104.8 Millimeter  |
| D                             | 5.188 Inch   131.775 Millimeter  |