

# NACHI NP 428 cylindrical roller bearings

100% Authentic. NACHI NP 428 cylindrical roller bearings  
TIMKEN Manufacturer Name Highest Quality. 0.0 Inventory  
Certified Supplier.

|                          |               |
|--------------------------|---------------|
| Inventory                | 0.0           |
| Manufacturer Name        | TIMKEN        |
| Minimum Buy Quantity     | N/A           |
| EAN                      | 0883450507363 |
| Weight / US pound        | 0.01          |
| Product Group            | M06110        |
| Shaft Size               | 2.362 in      |
| Shaft Size Type          | Metric        |
| Weight                   | 23 lb         |
| UPC Code                 | 0883450507363 |
| Type E Open Cover Number | EUDR-2 1/4    |
| Dimension B              | 4 in          |
| Dimension L              | 10-1/2 in     |
| Dimension A              | 2-7/8 in      |
| Dimension J Min.         | 8-3/8 in      |
| Dimension J Max.         | 8-5/8 in      |
| Bolt Diameter            | 5/8 in        |
| Dimension N              | 3/4 in        |
| Dimension N1             | 7/8 in        |
| Dimension H1             | 1-5/8 in      |
| Dimension H2             | 5-23/32 in    |
| Dimension d1             | 4-1/16 in     |

|  |   |
|--|---|
| Dimension H  | 2-3/4 in  |
| Dimension Ac   | 4.05 in   |
| Dimension d2   | 4.945 in  |
| e  | 0.40  |
| X (if $F_a/F_r \leq e$ )                                   | 0.87  |
| Y (if $F_a/F_r \leq e$ )                                   | 2.17  |
| X (if $F_a/F_r > e$ )                                      | 0.7   |
| Y (if $F_a/F_r > e$ )                                      | 2.63  |
| K Factor   | 1.51  |
| C90 Dynamic Load Rating <sup>1</sup>                       | 11600 lb  |
| C0 Static Load Rating                                      | 54000 lb  |
| Fa-max Maximum Permissible Thrust Load <sup>2</sup>        | 3454 lb   |
| Fr-max Maximum Allowable Slip Fit Radial Load <sup>3</sup> | 9500 lb   |
| Max. Speed <sup>4</sup>                                    | 2420 rpm  |
| Note   | Note: All units have a 1/8 pipe thread grease fitting<br>The Maximum Permissible Thrust Load applies to |