

NACHI NU 2226 cylindrical roller bearings

Browse NACHI NU 2226 cylindrical roller bearings Categories in the Manufacturers Online Free. including 150x225x67.5 Size (mm) .

Size (mm)	150x225x67.5
Bore Diameter (mm)	150
Outer Diameter (mm)	225
Width (mm)	67,5
d	150 mm
D	225 mm
H	67.5 mm
d1	184.9 mm
D1	206.2 mm
r1,2 – min.	2.1 mm
r3,4 – min.	1.1 mm
da – min.	161 mm
Da – max.	219 mm
ra – max.	2 mm
rb – max.	1 mm
dn	179.9 mm
Basic dynamic load rating – C	104 kN
Basic static load rating – C0	260 kN
Fatigue load limit – Pu	8 kN
Limiting speed for grease lubrication	4500 r/min
Limiting speed for oil lubrication	5300 mm/min
Preload class A	1300 N

Preload class B	3900 N
Static Axial rigidity, Preload class A	896 N/micron
Static Axial rigidity, Preload class B	1353 N/micron
Gref	80 cm
r1,2 min.	2.1 mm
r3,4 min.	1.1 mm
da min.	161 mm
Da max.	219 mm
ra max.	2 mm
rb max.	1 mm
Basic dynamic load rating C	104 kN
Basic static load rating C0	260 kN
Fatigue load limit Pu	8 kN
Attainable speed for grease lubrication	4500 r/min
Attainable speed for oil-air lubrication	5300 r/min
Static axial stiffnes for preload A	896 N/ μ m
Static axial stiffnes for preload B	1353 N/ μ m
Reference grease quantity Gref	80 cm ³
Mass bearing	9 kg