

NACHI NUP 1092 cylindrical roller bearings

Manufacturers of all are represented in our partial list of 70 mm d clients. Contact Gary for a complete NACHI NUP 1092 cylindrical roller bearings list of clients and projects.

d	70 mm
D	125 mm
B	31 mm
E	113.5 mm
F	83.5 mm
rs min	1.5 mm
r1s min	1.5 mm
Radial clearance class	C3
Mass (without HJ ring)	1.48 kg
Dynamic load, C	156 kN
Static load, C0	194 kN
Fatigue limit load, Cu	23.7 kN
Nlim (oil)	5,200 rpm
Nlim (grease)	4,500 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.41 Hz
Characteristic outer ring frequency, BPF0	7.21 Hz
Characteristic inner ring frequency, BRFI	9.79 Hz
da min	78 mm
da max	82 mm

db min	86 mm
Da max	117 mm
ra max	1.5 mm
r1a max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.506
EAN	4547359774733
Product Group	B04144