

NACHI NUP 2215 E cylindrical roller bearings

Enjoy High Margins on Competitive 75 Bore Diameter (mm) Pricing.Great 75x160x37 Size (mm) Wholesale Products at Low Costs.

Size (mm)	75x160x37
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Width (mm)	37
d	75 mm
D	160 mm
B	37 mm
C	37 mm
d1	101 mm
r1 min.	2,1 mm
r2 min.	2,1 mm
D2	139 mm
Weight	3,05 Kg
Temperature –	30 to +250 °
Basic static load rating (C0)	76,5 kN
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	75MM Bore; 160MM Outside Diameter; 37MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fi
Other Features	Deep Groove Extreme Temperature Variant
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	3.05
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.457 Inch 37 Millimeter
Bore	2.953 Inch 75 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
d1 ≈	101.4 mm
D2 ≈	138.4 mm
r1,2 min.	2.1 mm
da min.	87 mm
Da max.	148 mm
ra max.	2 mm

Basic dynamic load rating C	119 kN
Basic static load rating C ₀	76.5 kN
Limiting speed	70 r/min
Limiting temperature T max.	250 °C
Mass bearing	3.06 kg