

NACHI NUP 2248 cylindrical roller bearings

The 68 Outer Diameter (mm) online NACHI NUP 2248 cylindrical roller bearings parts store gives you immediate access to a 40x68x15 Size (mm) selection of more than 1.4 million new, used, remanufactured.

Size (mm)	40x68x15
Bore Diameter (mm)	40
Outer Diameter (mm)	68
Width (mm)	15
d	40 mm
D	68 mm
B	15 mm
C	15 mm
a	2.49 mm
b	1.9 mm
f	1.7 mm
r min.	1 mm
r1 min.	0.5 mm
D1	64.82 mm
D2	74.6 mm
Weight	0.186 Kg
Basic dynamic load rating (C)	16,8 kN
Basic static load rating (C0)	11,5 kN
(Grease) Lubrication Speed	9500 r/min
Inventory	0.0
Manufacturer Name	NACHI

Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 1 Metal Shield; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove With Snap Ring
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.4475
Outer Race Width	0.591 Inch 15 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.575 Inch 40 Millimeter
Outside Diameter	2.677 Inch 68 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	40 mm
Width	15 mm

Fillet Radius/Chamfer	1 mm
r1	0.5 mm
Snap Ring Width	1.7 mm
Snap Ring Outside Diameter	74.6 mm
D1 (max)	64.8 mm
a (max)	2.5 mm
b (min)	1.9 mm
Dynamic Load Rating	16,800 N
Static Load Rating	11,500 N
Limiting Speed – Grease	10,000 rpm
Limiting Speed – Oil	12,000 rpm
Factor fo	15.3
Radial Clearance	0.006 to 0.020 mm
da (min)	45 mm
Da (max)	63 mm
Dx (min)	76 mm
ra (max)	1 mm
Cy (max)	3.8 mm