

NACHI NUP 322 E cylindrical roller bearings

NACHI NUP 322 E cylindrical roller bearings, Units and Housings CAD models , Manufacturing Service . 30x72x19 Size (mm) Get 72 Outer Diameter (mm) Your Free.

| | |
|-------------------------------|-------------|
| Size (mm) | 30x72x19 |
| Bore Diameter (mm) | 30 |
| Outer Diameter (mm) | 72 |
| Width (mm) | 19 |
| d | 30 mm |
| D | 72 mm |
| B | 19 mm |
| C | 19 mm |
| r1 min. | 1.1 mm |
| da min. | 36.5 mm |
| Da max. | 65.5 mm |
| ra max. | 1.0 mm |
| Weight | 0.387 Kg |
| Basic dynamic load rating (C) | 21,3 kN |
| Basic static load rating (C0) | 6,3 kN |
| (Grease) Lubrication Speed | 9000 r/min |
| (Oil) Lubrication Speed | 11000 r/min |
| Calculation factor (e) | 0.26 |
| Calculation factor (Y0) | 2.52 |
| Calculation factor (Y1) | 2.40 |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |

| | |
|-------------------------|---|
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00152 |
| Mounting Method | Tapered Adapter |
| Enclosure | Open |
| Rolling Element | Ball Bearing |
| Adapter Sleeve | H-306X |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Internal Clearance | C0-Medium |
| Number of Rows of Balls | Double Row |
| Other Features | Allowable Misalignment 3 Deg 1:12 Taper |
| Long Description | 30MM Bore; Tapered Adapter Mount; 72MM Outside Diameter; 19MM Inner Race Width; 19MM Outer Race Width |
| Inch – Metric | Metric |
| UNSPSC | 31171532 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Self Aligning |
| Weight / LBS | 0.85319 |
| Inner Race Width | 0.748 Inch 19 Millimeter |
| Outside Diameter | 2.835 Inch 72 Millimeter |
| Outer Race Width | 0.748 Inch 19 Millimeter |
| Bore | 1.181 Inch 30 Millimeter |