

# NBS 89426-M thrust roller bearings

NBS 89426-M thrust roller bearings 120x260x86 Size (mm) with easy-to-use parts graphics, giving you the ability to check parts availability, 120 Bore Diameter (mm) pricing, examine remanufactured options.

|                     |            |
|---------------------|------------|
| Size (mm)           | 120x260x86 |
| Bore Diameter (mm)  | 120        |
| Outer Diameter (mm) | 260        |
| Width (mm)          | 86         |
| d                   | 120 mm     |
| D                   | 260 mm     |
| B                   | 86 mm      |
| B1                  | 14 mm      |
| B2                  | 26 mm      |
| D1                  | 218,7 mm   |
| Da max              | 246 mm     |
| d1                  | 168,1 mm   |
| da max              | 151 mm     |
| da min              | 134 mm     |
| dc min              | 171 mm     |
| E                   | 230 mm     |
| F                   | 154 mm     |
| r1 min              | 3 mm       |
| ra max              | 2,5 mm     |
| rmin                | 3 mm       |

|   |  |
|---|--|
| s   | 7,2 mm / Axial displacement facility from central position |
| – HJ2324-E /<br>Designation, L-section ring | HJ2324E / Designation, Lsection ring                       |
| m   | 23,8 kg / Weight   |
| m1  | 1,49 kg  |
| Cr  | 930000 N / Dynamic load rating (radial)                    |
| C0r   | 1010000 N / Static load rating (radial)                    |
| nG  | 3950 1/min / Limiting speed                                |
| nB  | 2010 1/min / Reference speed                               |
| Cur   | 166000 N / Fatigue limit load, radial                      |