

NBS HK 0408 TN needle roller bearings

Enjoy 6.35×7.938×9.525 Size (mm) High Margins on Competitive Pricing.Great Wholesale Products at Low Costs. 6,35 Bore Diameter (mm)

Size (mm)	6.35×7.938×9.525
Bore Diameter (mm)	6,35
Outer Diameter (mm)	7,938
Width (mm)	9,525
d	6,35 mm
D	7,938 mm
B	9,525 mm
c1 min	0,1 mm
c2 min	0,2 mm
M	– mm
Weight	0,0012 Kg
Basic dynamic load rating (C)	4,8 kN
c1 min.	0.1 mm
c1 max.	0.4 mm
c2 min.	0.2 mm
c2 max.	0.8 mm
$\alpha \pm 8$	20 °
Shaft diameter range min.	6.302 mm
Shaft diameter range max.	6.325 mm
Housing bore range min.	7.93 mm
Housing bore range max.	7.945 mm

Basic dynamic load rating – radial direction C	4.8 kN
Basic static load rating – radial direction C ₀	15 kN
Specific dynamic load factor K	80 N/mm ²
Specific static load factor K ₀	250 N/mm ²
Factor depending on material and bearing type K _M	480
Permissible sliding velocity v min.	0 m/s
Permissible sliding velocity v max.	2 m/s
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Mass bushing	0.0012 kg