

NBS K 12x15x9 TN needle roller bearings

100% Authentic. NBS K 12x15x9 TN needle roller bearings
Highest 12.0 Inventory TIMKEN Manufacturer Name Quality.
Certified Supplier.

Inventory	12.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	12 lb
EAN	0053893534442
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-7/8" Bore; 6.2" Bolt Circle; 4-3/8" Bolt Spacing; 1 Pie

Other Features	Double Row Wide Inner Race With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	E-4BF-TRB-1 7/8
Weight / LBS	12
Nominal Bolt Circle Diameter Round	6.2 Inch 157 Millimeter
D	3.5 Inch 88.9 Millimeter
Bolt Spacing	4.375 Inch 111.13 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
d	1.875 Inch 47.625 Millimeter
Shaft Size	1.875 in
Shaft Size Type	Imperial
UPC Code	053893534442
Dimension B	3-1/2 in
Dimension L	5-5/8 in
Dimension A	3-3/32 in
Dimension J	4-3/8 in
Dimension A2	1/8 in
Bolt Diameter	1/2 in
Dimension A1	1-3/16 in
Dimension D 1	4-7/16 in
Dimension d1	3-7/16 in
e	0.33

X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	2.64
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	3.18
K Factor	1.83
C90 Dynamic Load Rating ²	10300 lb
C0 Static Load Rating	43000 lb
Fa-max Maximum Permissible Thrust Load ³	2590 lb
Fr-max Maximum Allowable Slip Fit Radial Load ⁴	8400 lb
Max. Speed ⁵	3050 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to