## NBS K 36x41x30 needle roller bearings

170 Million used NBS K 36x41x30 needle roller bearings instantly searchable. Shop our large selection of parts based TIMKEN Manufacturer Name on brand, price, description, and location. Order the with stock … 0.0 Inventory N/A Minimum Buy Quantity

| Inventory                 | 0.0                       |
|---------------------------|---------------------------|
| Manufacturer Name         | TIMKEN                    |
| Minimum Buy Quantity      | N/A                       |
| Weight                    | 18.614                    |
| EAN                       | 0883450097529             |
| Product Group             | M06288                    |
| Number of Mounting Holes  | 2                         |
| Mounting Method           | Eccentric Collar          |
| Housing Style             | 2 Bolt Pillow Block       |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel                |
| Expansion / Non-expansion | Non-expansion             |
| Mounting Bolts            | 20 Millimeter             |
| Relubricatable            | Yes                       |
| Insert Part Number        | 22215                     |
| Seals                     | Double Lip Nitrile Rubber |
| Housing Configuration     | 1 Piece Solid             |
| Inch — Metric             | Metric                    |
| Other Features            | Double Row   SN Style     |

| Long Description              | 2 Bolt Pillow Block; 75MM Bore;<br>95MM Base to Center Height;<br>Eccentric Collar Mount;<br>Spherical Roller |
|-------------------------------|---|
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | QMSN15J075SB  |
| Weight / LBS                  | 46  |
| D                             | 3.622 Inch   92 Millimeter  |
| Nominal Bolt Center to Center | 10.2 Inch   260 Millimeter  |
| Bolt Spacing Minimum          | 9.488 Inch   241Millimeter  |
| Bolt Spacing Maximum          | 10.984 Inch   279Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   OMillimeter  |
| d                             | 2.953 Inch   75 Millimeter  |
| В                             | 3.74 Inch   95 Millimeter   |