

NBS NA 6911 ZW needle roller bearings

Request A Quote For Your Special NBS NA 6911 ZW needle roller bearings Needs Today! Free Quotes. ISO 9001 certified. 90 mm d 30 mm B

| | |
|---|-----------|
| d | 90 mm |
| D | 160 mm |
| B | 30 mm |
| E | 145 mm |
| F | 107 mm |
| rs min | 2 mm |
| r1s min | 2 mm |
| Radial clearance class | C3 |
| Mass (without HJ ring) | 2.3 kg |
| Dynamic load, C | 182 kN |
| Static load, C0 | 217 kN |
| Fatigue limit load, Cu | 24.7 kN |
| Nlim (oil) | 4,600 rpm |
| Nlim (grease) | 3,900 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.42 Hz |
| Characteristic rolling element frequency, BSF | 6.48 Hz |
| Characteristic outer ring frequency, BPF0 | 7.22 Hz |
| Characteristic inner ring frequency, BRFI | 9.78 Hz |
| da min | 99 mm |
| da max | 105 mm |

| | |
|----------------------|---------------|
| db min | 109 mm |
| Da max | 151 mm |
| ra max | 2 mm |
| r1a max | 2 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 2.464 |
| EAN | 4547359140118 |
| Product Group | B04144 |