## NBS NAO 25x40x17 needle roller bearings

Advance NBS NAO 25x40x17 needle roller bearings is your source for quality and 0.0 Inventory accessories. shop online for home delivery or pick up in one of our 10000 . TIMKEN Manufacturer Name

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 4.99  |
| EAN                       | 0883450966047   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22209   |
| Seals                     | Triple Lip Viton  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch — Metric             | Inch  |
| Long Description          | 4 Bolt Square Flange Block;<br>1-3/4" Bore; 5.8" Bolt Circle;<br>4-1/8" Bolt Spacing; 1 Pie |

| Other Features                        | Double Row   Single Collar  <br>With Set Screw |
|---------------------------------------|--|
| UNSPSC                                | 31171501                                       |
| Harmonized Tariff Code                | 8483.20.40.80                                  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | QAF09A112SEN                                   |
| Weight / LBS                          | 11   |
| Nominal Bolt Circle Diameter<br>Round | 5.8 Inch   148 Millimeter                      |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                          |
| D                                     | 2.88 Inch   73.152 Millimeter                  |
| d                                     | 1.75 Inch   44.45 Millimeter                   |
| Bolt Spacing                          | 4.125 Inch   104.78 Millimeter                 |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                          |