

NBS SCV 25 linear bearings

100% Authentic. NBS SCV 25 linear bearings Highest Quality. 40 mm d Certified Supplier.

d	40 mm
D	68 mm
B	15 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.19 kg
Dynamic load, C	16.8 kN
Static load, C0	11.5 kN
Fatigue limit load, Cu	0.52 kN
f0	15.2
Nlim (grease)	10,000 rpm
Min operating temperature, Tmin	-30 °C
Max operating temperature, Tmax	175 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.66 Hz
Characteristic outer ring frequency, BPF0	5.12 Hz
Characteristic inner ring frequency, BRFI	6.88 Hz
da min	45 mm
Da max	63 mm
ra max	1 mm
Inventory	0.0

Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.186
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Chevron SRI2 Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.4541
Outside Diameter	2.677 Inch 68 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
Bore	1.575 Inch 40 Millimeter