

# NBS SCW 40 AS linear bearings

100% 0.0 Inventory REGAL BELOIT Manufacturer Name Authentic.  
N/A Minimum Buy Quantity NBS SCW 40 AS linear bearings Highest  
Quality. Certified Supplier.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REGAL BELOIT  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 2.452   |
| EAN                       | 0662461052525   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Flange Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 19/32 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 5210  |
| Seals                     | Felt Labyrinth  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 2 Bolt Flange Block; 50MM Bore; 157MM Bolt Circle; 157.175MM Bolt Spacing; 1 Piece Solid; Set Screw |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Standard Duty   Has Flinger |
| UNSPSC                             | 31171501                                 |
| Harmonized Tariff Code             | 8483.20.40.40                            |
| Noun                               | Bearing                                  |
| Keyword String                     | Flanged                                  |
| Manufacturer Item Number           | SFT-210                                  |
| Manufacturer Internal Number       | 710024                                   |
| Weight / LBS                       | 5.4                                      |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter                    |
| D                                  | 2.031 Inch   51.6 Millimeter             |
| Bolt Spacing                       | 6.188 Inch   157.175 Millimeter          |
| d                                  | 1.969 Inch   50 Millimeter               |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter                    |
| Nominal Bolt Circle Diameter Round | 6.2 Inch   157 Millimeter                |