

# NBS SL183014 cylindrical roller bearings

NBS SL183014 cylindrical roller bearings Deal is your source for OEM 0.0 Inventory and accessories. We sell Genuine at discount prices.

|                           |                                  |
|---------------------------|----------------------------------|
| Inventory                 | 0.0                              |
| Manufacturer Name         | REXNORD                          |
| Minimum Buy Quantity      | N/A                              |
| Weight                    | 5.053                            |
| EAN                       | 0793699529128                    |
| Product Group             | M06288                           |
| Number of Mounting Holes  | 2                                |
| Mounting Method           | Tapered Adapter Sleeve           |
| Housing Style             | 2 Bolt Pillow Block              |
| Rolling Element           | Spherical Roller Bearing         |
| Housing Material          | Cast Iron                        |
| Expansion / Non-expansion | Non-expansion                    |
| Mounting Bolts            | 5/8 Inch                         |
| Relubricatable            | Yes                              |
| Insert Part Number        | B22631E7L                        |
| Seals                     | Triple Lip Contact               |
| Housing Configuration     | 1 Piece Solid                    |
| Inch – Metric             | Inch                             |
| Other Features            | Double Row   Extended Inner Race |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-15/16" Bore; 2-1/4" Base to Center Height; Tapered Adapter Sleeve M |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | EPB22631E7   |
| Manufacturer Internal Number  | 0152912  |
| Weight / LBS                  | 12   |
| B                             | 2.25 Inch   57.15 Millimeter   |
| D                             | 3.08 Inch   78.232 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Minimum          | 6.063 Inch   154Millimeter   |
| d                             | 1.938 Inch   49.225 Millimeter   |
| Nominal Bolt Center to Center | 6.6 Inch   167 Millimeter  |
| Bolt Spacing Maximum          | 7.25 Inch   184.15Millimeter   |